

SM 2289

DIN 911D / ISO 2936D

Sechskantschraubendreher

metrisch
Hexagon socket screw keys (metric)



Catalog No.	SW
SM 2289	01.3



Chrom-Vanadium, gehärtet und vernickelt, Stirnflächen plan bearbeitet, Stirnkanten gefast

Chrom-Vanadium, hardened and nickel-coated, end face machined, edges of end face chamfered.



mm



SW	€	VPE	Höhe <i>high</i>	Länge <i>long</i>	kg
01,3	0,76	2	12	40	0,001
01,5	0,32		14	45	0,001
02,0	0,35		16	50	0,002
02,5	0,36		18	56	0,003
03,0	0,43		20	63	0,005
04,0	0,53		25	70	0,010
05,0	0,76		28	80	0,018
06,0	1,01		32	90	0,030
07,0	1,39		34	95	0,043
08,0	1,63		36	100	0,059
09,0	2,11	1	38	105	0,079
10,0	2,50		40	112	0,103
11,0	3,05		42	118	0,131
12,0	4,06		45	125	0,160
14,0	6,34		56	140	0,260
17,0	9,79		63	160	0,430
19,0	12,54		70	180	0,617
22,0	21,60		80	200	0,920

3

SM 2300

DIN 6911D

Winkelschraubendreher mit Zapfen

metrisch
Hexagon-socket screw keys (metric) with pilot



Catalog No.	SW
SM 2300	03



mit Zapfen für Schrauben DIN 6912, Chrom-Vanadium, gehärtet und vernickelt
with pin for DIN 6912 screws, Chrom-Vanadium, hardened and nickel-coated.



mm



SW	€	VPE	Höhe <i>high</i>	Länge <i>long</i>	kg
03	1,09	2	20	63	0,005
04	1,30		25	71	0,010
05	1,63		28	80	0,018
06	1,76		32	90	0,030
08	2,20		36	100	0,059
10	3,65	1	40	112	0,103
12	5,20		45	125	0,160
14	8,02		56	140	0,260
17	13,08		63	160	0,430