



	Catalog No.	Form	d₁	X	l₁
	SM 1000-1	A	01.90	X	06



Quantity discount rate

Ab Menge	50 - 99	100 - 199	200 - 499	500 <
Rabatt	5%	15%	20%	30%

Pro Abmessung / Per size



Spezialstahl
 special steel



gehärtet und geschliffen
 hardened and ground



HRc = 63 - 65



mm



0,1; 0,25; 0,75 mm



Form B = +10% / form B = +10%.

Zwischenmaße: Nach DIN ist bis zum Innendurchmesser 15,0 mm eine Stufung von 0,1 mm vorgesehen. Über 15,0 mm beträgt die Stufung 0,5 mm. Für abweichende Bohrungsdurchmesser berechnen wir folgende Zuschläge pro Abmessung:

Intermediate sizes: according to DIN a grading of 0,1 mm is provided for an inner diameter of up to 15,0 mm. Over and above 15,0 mm the grading is 0,5 mm. For deviating diameters we impose the following surcharges per dimension:

1 - 2 Stück / pieces = 200%	25 - 49 Stück / pieces = 10%
3 - 5 Stück / pieces = 150%	50 - 99 Stück / pieces = 5%
6 - 9 Stück / pieces = 75%	ab 100 Stück / pieces and more = 0%.
10 - 24 Stück / pieces = 20%	



andere Materialien und Abmessungen
 Preise unter 25 Stück

other material and dimensions
 Prices for less than 25 pieces



Form A



Form B



Reinigen mit
SM 1306
 Clean with
 Seite 360



Eingießen mit
SM 1304
 Pour in with
 Seite 359



d ₁ F7 Ø	d ₂ Ø -0,03	€			l ₃	r	l ₂	t
		l ₁ kurz short	l ₁ mittel medium	l ₁ lang long				
01,00 - 01,80	04	06	2,41	08	1,00	1,0	1,0	0,5
01,90 - 02,60	05		1,82	09				
02,70 - 03,30	06	08	1,87	12	1,25	1,5	1,5	1,0
03,40 - 04,00	07		1,90					
04,10 - 05,00	08		2,05					
05,10 - 06,00	10	10	2,16	16	1,50	2,0	2,0	1,0
06,10 - 08,00	12		2,39					
08,10 - 10,00	15	12	2,66	20	1,50	2,0	2,0	1,0
10,10 - 12,00	18		2,94					
12,10 - 15,00	22	16	3,26	28	1,50	3,0	2,0	1,0
15,10 - 18,00	26		3,96					
18,10 - 22,00	30	20	5,25	36				