



Catalog No.	l_1	d_1 / d_2	Material	Colour
SM 1182	22	M03	NI	SW



Griffkörper: Zink-Druckguss, kunststoffbeschichtet

Buchse / Gewindebuchse und Halteschraube:

ST: Stahl, brüniert

NI: Edelstahl rostfrei 1.4305

handle: zinc die casting plastic coated

bushing / thread insert

and retaining screw:

ST: steel blackened

NI: stainless steel 1.4305



RH = unlackiert / uncoated

CR = verchromt / chrome-plated

kunststoffbeschichtet / plastic coated:

OR = orange RAL 2004

RS = rot strukturmatt / red textured finish RAL 3000

SB = silber / silver RAL 9006

SW = schwarz - strukturmatt / black textured finish RAL 9005

SZ = schwarz - seidenglanz / black silk finish RAL 9005



mm



Hebelverstellung durch Anheben des Griffes. Beim Loslassen rastet der Griff selbstständig wieder ein. Gewindeinsatz mit Griff durch Korbverzahnung lösbar verbunden.

Pulling the lever, disengages the serrations and allowing it to swivel to the ideal clamping position. On releasing the lever the serrations automatically re-engage.

l_1	$d_1 \varnothing$ Gewinde / thread		$d_2 H7 \varnothing$ Bohrung / hole		d_3	d_4	h_1	h_2	h_3	h_4 Rastweg groove way	t	kg
	ST	NI	ST	NI	$\varnothing$	$\varnothing$						
22	M03	M03	-	-	8	10,5	18,5	2	23	3	5	0,013
	M04	M04	B04	-								0,013
	M05	M05	B05	-								0,012
30	M03	M03	-	-	10	13	24,5	4	31	3,5	7	0,024
	M04	M04	-	-								0,023
	M05	M05	B05	-							9	0,022
	M06	M06	B06	-								0,021