



Catalog No. **Form** **d₁**
SM 1200 C 050



Grauguss
cast iron



entgratet, gerommelt
fettled and tumbled




kunststoffbeschichtet, Aluminium
plastic coated, aluminium





mm




d ₁ Ø	d ₄ Ø	h ₁	h ₂	kg ≈ A
Form A				
032	12	21	10	0,037
040	14	26	14	0,063
050	18	34	20	0,125
063	20	42	25	0,220
080	25	52	30	0,430
100	32	65	38	0,750




Form A




Form B



Form D



Form C



Form E



Form A: Rohteil / casting only
Form B: durchgebohrt / through bore
Form C: Sackloch / blind bore
Form D: Gewinde, durchgebohrt / threaded through bore
Form E: Gewindegewinde / threaded blind bore





d ₁ Ø	d ₄ Ø	d ₃ H7 Ø	d ₃ H7 Ø	d ₂ Ø	d ₂ Ø	h ₁	h ₂	t ₁ min	t ₂	kg ≈ B/C	kg ≈ D/E
		Form B	Form C	Form D	Form E						
032	12	B06	B06	M06	M06	20	9	12	10	0,031	0,032
040	14	B08	B08	M08	M08	25	13	15	13	0,053	0,055
050	18	B10	B10	M10	M10	32	18	18	16	0,101	0,105
063	20	B12	B12	M12	M12	40	23	22	20	0,180	0,195
080	25	B16	B16	M16	M16	50	28	28	20	0,360	0,380
100	32	B20	B20	M20	M20	63	36	36	25	0,670	0,720

SM 1200-1

DIN 6335

Kreuzgriffschraube Grauguss

Palm grip screw, cast iron



Catalog No. **d₁** **d₂** **X** **l**
SM 1200-1 040 M08 X 40



Grauguss, Stahlschraube brüniert
cast iron, steel screw blackened



sauber entgratet, Grauguss gerommelt
fettled and tumbled



Die Schraube ist eingeschraubt und durch einen Querstift gesichert.
The threaded stud is screwed in and secured by a cross-dowel.



mm



d ₁ Ø	d ₂ Ø	l							d ₄ Ø	h ₁	h ₂
032	M06	16	20	25	30	35	45		12	20	9
040	M08	15	20	25	30	40	55		14	25	13
050	M10	-	25	30	35	45	55		18	32	18
063	M12	-	30	35	40	50	60		20	40	23
080	M16	-	30	40	50	60	70		25	50	28