





Form A




Form C



Form D



Form E



Catalog No.	Form	d ₁	d ₂ / d ₃	Surface
SM 1205-2	D	40	M08	MT



Aluminium, geschmiedet
aluminium, forged



MT: matt (GLEITSchliff),
Trennnaht nicht sichtbar / matt, tumbled
PL: poliert (nur Form C / D / E) /
polished (only type C / D / E)
Form A: unbearbeitet / surface untreated



Form A: Rohteil / without bore
Form C: Sackloch, Bohrung H7 / blind bore H7
Form D: Gewinde, durchgebohrt / threaded through bore
Form E: Gewindesackloch / threaded blind bore



mm



d ₁ Ø	d ₄ Ø	h ₃	h ₄ min.	kg
Form A				
40	14	26	13	0,030
50	18	34	17	0,057
63	20	42	21	0,097
80	25	52	25	0,250




d ₁ Ø	d ₂ Ø	d ₃ H7 Ø	d ₄ Ø	h ₁	h ₂ min.	t ₁ min.	t ₂	kg	
	Form D / E MT / PL	Form C MT / PL						D	C / E
40	M08	B08	14	25	12	15	13	0,032	0,025
50	M08 / M10	B08 / B10	18	32	15	18	16	0,065	0,050
63	M10 / M12	B10 / B12	20	40	19	22	20	0,118	0,120
80	M12 / M16	B12 / B16	25	50	23	28	20	0,230	0,235


SM 1205-3

Sterngriff Edelstahl rostfrei


Star knob, stainless steel



Form A



Form B



Catalog No.	Form	d ₁	d ₂ / d ₃
SM 1205-3	B	40	M08



Edelstahl rostfrei 1.4301, matt gestrahlt
stainless steel AISI 304, matt shot-blasted



Griff aus Edelstahl-Blech gezogen,
matt gestrahlt,
Nabe stumpf aufgeschweißt
Hub butt-welded,
matt shot-blasted,
knob drawn from stainless steel-sheet.



Form A: Sackloch / blind bore
Form B: Gewindesackloch / threaded blind bore



mm



Edelstahl rostfrei 1.4404 (A4) /
stainless steel AISI 316L



d ₁ Ø	d ₂ Ø	d ₃ H7 Ø	d ₄ Ø	h ₁ ≈	h ₂ ≈	t min.	kg
	Form B	Form A					
32	M05 / M06	B06	12	21,0	10,0	12	0,026
40	M06 / M08	B08	14	24,0	12,0	15	0,037
50	M08 / M10	B10	18	30,0	16,5	18	0,067
60	M10 / M12	B12	20	37,5	20,0	22	0,104