



SM 1080

DIN 6316

Spanneisen einfach gekröpft

Clamp with goose-neck



Catalog No.	b ₁	X	l	Material
SM 1080	22	X	160	ST



Vergütungsstahl, lackiert
heat treated steel, varnished



mm



Aluminium



* Abmessungen nicht nach DIN
dimensions not according to DIN




b ₁	l	a	b ₂	b ₃	c	e ₁	e ₂	h	für Nuten- schrauben/ T-bolt SM 1105	kg
06,6	060	10	20	10	8	22,0	20	9	M6	0,080
09	080	12	25	12	9	27,5	25	11	M8	0,167
11	100	15	30	15	12	36,0	32	14	M10	0,300
14	125	20	40	20	16	44,0	40	18	M12, M14	0,680
18	125*	25	50	25	20	51,5	40	23	M16, M18	1,050
	160						50	23	M16, M18	1,370
22	160*	30	60	30	25	59,0	55	27	M20, M22	1,912
	200						70	27	M20, M22	2,417
26	200*	35	70	35	28	76,5	60	32	M24	3,315
	250						80	32	M24	4,135
33	250*	40	80	40	40	96,0	80	45	M30	5,226
	315						100	45	M30	8,460
43	400	60	100	50	50	105,0	120	55	M36, M42	17,080

SM 1083

Spanneisen verstellbar, gerade

Adjustable plain clamp with adjusting screw



Catalog No.	Form	a
SM 1083	B	12




Vergütungsstahl, lackiert
heat treated steel, varnished



andere Größen
other dimensions



mm



a	h	äuhl. / like DIN 6314 b ₁ x l	SM 1105 T-Nutenschraube T-bolts	d	e ₁	e ₂	kg
Form A							
10	8 - 37	11 x 80	-	M10	15	30	0,200
12 + 14	10 - 47	14 x 100	-	M12	21	40	0,560
16 + 18	13 - 52	18 x 125	-	M16	26	45	1,110
20 + 22	16 - 65	22 x 160	-	M20	30	60	2,050
24	20 - 83	26 x 200	-	M24	35	80	3,200
Form B							
10	8 - 32	11 x 80	M10 x 10 x 080	M10	15	30	0,340
12	10 - 40	14 x 100	M12 x 12 x 100	M12	21	40	0,700
14	10 - 38		M12 x 14 x 100				0,720
16	13 - 48	18 x 125	M16 x 16 x 125	M16	26	45	1,400
18	13 - 46		M16 x 18 x 125				1,400
20	16 - 65	22 x 160	M20 x 20 x 160	M20	30	60	2,600
22			M20 x 22 x 160				2,770