



* oder 120° für kurze Längen.
or 120° for short length.



Bis M05
up to M05

Ab M06
from M06



Catalog No.	d	X	I	Material
SM 1291-05	M06	X	10	ST



ST: Stahl, verzinkt / steel, zinc plated



Festigkeitsklasse 45H
grade 45H



mm



Reinigen mit
SM 1306
Clean with



Kleben mit
SM 1301
Lock with

d ₁ Ø	-	-	-	1,5	2,0	3,0
t	1,2	1,5	2,0	2,0	3,0	4,0
SW	1,5	2,0	2,5	3,0	4,0	5,0
I	d Ø					
05	M03	M04	M05	-	-	-
06	M03	M04	M05	M06	-	-
08	M03	M04	M05	M06	M08	-
10	M03	M04	M05	M06	M08	M10
12	M03	M04	M05	M06	M08	M10
16	M03	M04	M05	M06	M08	M10
20	M03	M04	M05	M06	M08	M10
25	-	M04	M05	M06	M08	M10
30	-	-	M05	M06	M08	M10
35	-	-	-	M06	M08	M10
40	-	-	-	M06	M08	M10
45	-	-	-	M06	M08	M10
50	-	-	-	M06	M08	M10
60	-	-	-	M06	M08	M10
70	-	-	-	-	-	M10
80	-	-	-	-	-	M10

—Sonderteilefertigung nach Ihren Zeichnungen und Mustern
Alteration service according to your drawings and models

