



Catalog No. **SM 4070** **12 X 080**



Stahl 1.7139 gehärtet, HRC 60±1
steel, hardened HRC 60±1



mm



andere Abmessungen
other dimensions



CAD-Daten verfügbar
CAD-files available



D Ø g6	L 0 -0,5	d Ø	l	h 0 -0,2	kg kg
08	040	10	4	3	0,016
	050	10		3	0,020
	060	10		3	0,024
	080	10		3	0,032
	100	10		3	0,040
09	040	12	4	3	0,020
	060	12		3	0,031
	080	12		3	0,040
	100	12		3	0,050
	120	12		3	0,060
10	040	12		3	0,025
	060	12		3	0,037
	080	12		3	0,049
	100	12		3	0,062
	120	12		3	0,074
	140	12		3	0,086
12	040	16	5	3	0,098
	060	16		6	0,039
	080	16		6	0,056
	100	16		6	0,074
	120	16		6	0,092
	140	16		6	0,110
	160	16		6	0,127
	180	16		6	0,144
14	040	18	5	6	0,162
	060	18		6	0,180
	080	18		8	0,077
	100	18		8	0,101
	120	18		8	0,125
	140	18		8	0,150
	160	18		8	0,173
	180	18		8	0,197
	200	18		8	0,221
	220	18		8	0,245
15	040	18	5	8	0,270
	060	18		8	0,293
	080	18		8	0,086
	100	18		8	0,114
	120	18		8	0,142
	140	18		8	0,170
	160	18		8	0,197
	180	18		8	0,224
	200	18		8	0,252
	220	18		8	0,280
16	040	20	5	8	0,307
	060	20		8	0,335
	080	20		8	0,069
	100	20		8	0,100
	120	20		8	0,136
	140	20		8	0,163
	160	20		8	0,194
	180	20		8	0,226
16	040	20	5	8	0,257
	060	20		8	0,100
	080	20		8	0,136
	100	20		8	0,163
	120	20		8	0,194
	140	20		8	0,226
	160	20		8	0,257
	180	20		8	0,289

D Ø g6	L 0 -0,5	d Ø	l	h 0 -0,2	kg kg
16	180	20	5	8	0,288
	200	20		8	0,320
	220	20		8	0,351
	240	20		8	0,382
	300	20		8	0,476
	360	20		8	0,570
18	060	22	7	8	0,125
	080	22		8	0,164
	100	22		8	0,204
	120	22		8	0,244
	140	22		8	0,283
	160	22		8	0,323
	180	22		8	0,363
	200	22		8	0,402
	220	22		8	0,442
	240	22		8	0,482
20	060	24	7	8	0,521
	080	24		8	0,561
	100	24		8	0,600
	120	24		8	0,640
	140	24		8	0,680
	160	24		8	0,720
	180	24		8	0,760
	200	24		8	0,800
	220	24		8	0,840
	240	24		8	0,880
22	060	26	7	8	0,920
	080	26		8	0,960
	100	26		8	1,000
	120	26		8	1,040
	140	26		8	1,080
	160	26		8	1,120
	180	26		8	1,160
	200	26		8	1,200
	220	26		8	1,240
	240	26		8	1,280
24	080	28	7	15	0,252
	100	28		15	0,311
	120	28		15	0,370
	140	28		15	0,429
	160	28		15	0,488
	180	28		15	0,547
24	080	28	7	15	0,606
	100	28		15	0,665
	120	28		15	0,724
	140	28		15	0,783
	160	28		15	0,842
	180	28		15	0,901

D Ø g6	L 0 -0,5	d Ø	l	h 0 -0,2	kg kg
24	160	28	7	15	0,651
	180	28		15	0,651
	200	28		15	0,721
	220	28		15	0,792
	240	28		15	0,863
	260	28		15	0,933
	280	28		15	1,004
	300	28		15	1,074
	320	28		15	1,145
	340	28		15	1,215
30	100	36	7	15	1,286
	120	36		15	0,583
	140	36		15	0,694
	160	36		15	0,804
	180	36		15	0,914
	200	36		15	1,024
	220	36		15	1,135
	240	36		15	1,245
	260	36		15	1,355
	280	36		15	1,465
32	100	36	7	15	1,575
	120	36		15	0,647
	140	36		15	0,773
	160	36		15	0,898
	180	36		15	1,024
	200	36		15	1,150
	220	36		15	1,275
	240	36		15	1,400
	260	36		15	1,526
	280	36		15	1,651
40	100	48	10	15	1,776
	120	48		15	1,902
	140	48		15	2,028
	160	48		15	2,154
	180	48		15	2,280
	200	48		15	2,406
	220	48		15	2,532
	240	48		15	2,658
	260	48		15	2,784
	280	48		15	2,910
50	100	58	15	15	3,036
	120	58		15	3,162
	140	58		15	3,288
	160	58		15	3,414
	180	58		15	3,540
	200	58		15	3,666
	220	58		15	3,792
	240	58		15	3,918
	260	58		15	4,044
	280	58		15	4,170
60	100	68	15	15	4,296
	120	68		15	4,422
	140	68		15	4,548
	160	68		15	4,674
	180	68		15	4,800
	200	68		15	4,926