



Catalog No. Form d₁
SM 1273-69 B 10



Edelstahl rostfrei 1.4305
stainless steel 1.4305



für Kugelsperr- und Steckbolzen

Form A: mit Außensechskant

Form B: mit Innensechskant

Form C: plan, mit Stirnbohrung
gute Zentriermöglichkeit durch genauen
Bund,
gut einsetzbar bei dünnwandigen
Bauteilen,
beidseitig einsetzbar

Montage

Die Ausführung mit Stirnlochbohrung
(Form C) kann mit einem gekröpften
Stirnlochschlüssel (SM 1273-67 STV 2)
oder mit einem Stirnloch-Steckschlüssel
(SM 1273-67 STS 4 oder SM 1273-67
STS 5) montiert werden.



Form A: with outer hexagon

Form B: internal hexagon

Form C: plain, with front hole optimized
centering due to precise collar
can be used in thin-walled pieces
application from both sides

Assembly

This design with holes on the front face
(form C) can be installed via a cranked
pin face spanner (SM 1273-67 STV 2)
or alternatively via a pin faced socket
wrench (SM 1273-67 STS 4 oder SM
1273-67 STS 5).



mm



d ₁	d ₂	d ₃	d ₄	d ₅	l ₁	l ₂	l ₃	l ₄	l ₇	SW	für Kugelsperr- und Steckbolzen	kg
Ø	Ø	Ø	Ø	Ø							for ball lock pins and socket pins	
H11		h9										
Form A											SM 1273-70 SM 1273-71 SM 1273-72 SM 1273-8 SM 1273-81 SM 1273-82 SM 1273-83 SM 1273-85	
16	M30	36	19,5	-	39	29	15,5	23,5	-	24		0,125
20	M36	45	25,5	-	49	38	17,5	31,5	-	30		0,208
25	M42	50	32,0	-	65	50	26,5	38,5	-	36		0,415
Form B												
05	M12	18	6,0	-	19	15	9,0	13,0	-	5		0,015
06	M12	18	7,5	-	19	15	9,4	13,0	-	6		0,013
08	M16	22	10,0	-	25	20	12,0	17,0	-	8		0,028
10	M24	30	12,5	-	29	24	13,5	19,5	-	10		0,075
12	M24	30	15,0	-	29	24	14,0	20,0	-	12		0,066
Form C												
16	M30	36	19,5	5,1	39	33	15,5	23,5	30	24	0,124	
20	M36	45	25,5	5,1	49	42	17,5	31,5	30	30	0,208	
25	M42	50	32,0	5,1	65	57	26,5	38,5	36	36	0,415	