

Catalog No.	Size
SM 2240	4



Stahl, verzinkt und passiviert
steel tempered, galvanized and
passivated



mm



Reinigen mit
SM 1306
Clean with




Sichern mit
SM 1301
Lock with

Größe Size	G ₁ x L	h		G ₂	B	L ₁	Schutz- kappe	kg
		min.	max.					
3	M05 x 90	39	52	M08	14,5	5	SM 2250 M05	0,055
4	M05 x 90	40	53	M08	18,5	5	SM 2250 M05	0,063
5	M05 x 90	40	48	M08	20,5	5	SM 2250 M05	0,064
6	M08 x 123	60	68	M12	24,0	7	SM 2250 M08	0,180

Anwendungsmöglichkeiten / Examples:

Andrückschraube Clamping screw Größe / Size	SM 2000	SM 2010	SM 2020	SM 2180	SM 2090	SM 2100	SM 2110	SM 2260
3	3	3	3	3	3	3	3	3
4	4	4	-	4	4	4	-	4
5	-	-	-	-	5	5	-	5
6	5 + 6	5 + 6	-	-	-	-	-	6



Catalog No.	Size
SM 2250	1



ölbeständiges Neopren,
zum Schutz empfindlicher Werkstücke.
Passend für Andrückschrauben SM 2200,
SM 2205, SM 2220 und SM 2240.
Of oil resistant Neopren to prevent damage to
delicate components.
Fits the clamping screw SM 2200, SM 2205,
SM 2220 and SM 2240.



* nach neuer Norm ISO 4017, gekenn-
zeichnet mit einer „6“ auf der
Andrückfläche
** nach alter Norm DIN 933
* According to new standard ISO 4017,
marked with a „6“ on its clamping face.
** According to old norm DIN 933.




mm



Reinigen mit
SM 1306
Clean with



Sichern mit
SM 1301
Lock with



Größe Size	SW	Gewinde Thread	l	d ₁ Ø	d ₂ Ø	kg
0	07	M04	8,5	07	11,0	0,001
1	08	M05	10,0	08	12,5	0,001
2	10	M06	12,0	10	15,0	0,002
3 + 4	13	M08	15,0	13	19,0	0,004
5	16	M10	17,5	15	22,0	0,005
6	18 *	M12	20,0	18	25,0	0,010
7	19 **	M12	20,0	19	26,0	0,010
8	24	M16	27,0	24	33,0	0,019