



Catalog No.	Form	l_1	d_1	X	l_2
SM 1720	IS	63	M06	X	20


Griffkörper:
Zink-Druckguss
kunststoffbeschichtet
silber, RAL 9006, strukturmatt

Schraubeneinsatz und Halteschraube
Edelstahl
nichtrostend, 1.4305

Handle:
zinc die casting
powder coated
silver, RAL 9006, textured finish

Threaded insert and retaining screw
stainless steel 1.4305 (AISI 303)

mm



verstellbarer Klemmhebel
SM 1720 oder SM 1721 /
adjustable hand lever

Winkel-Klemmverbinder
SM 1706 /
T-angle connector clamp

verstellbarer Klemmhebel
SM 1720 oder SM 1721 /
adjustable hand lever

Flansch-Klemmverbinder
SM 1704 /
Flanged connector clamp

Technical drawing showing the dimensions and components of the SM 1720 lever and its application to a tube clamp connector. The drawing includes the following labels:

- l_1 : Length of the lever arm.
- h_1 : Height of the lever arm at the base.
- h_2 : Height of the lever arm at the end.
- d_1 : Diameter of the lever arm at the base.
- d_2 : Diameter of the lever arm at the end.
- Rohr-Klemmverbinder mit Standard-Senkung / Tube clamp connector with standard counterbore
- Kerbverzahnung / Serrations

Form IS: mit Innensechskant

Verstellbare Klemmhebel SM 1720 ersetzen bei Rohr-Klemmverbindern die Innensechskantschrauben DIN 912.

In den Maßtabellen der Klemmverbinder finden Sie für jede Schraubstelle eine Empfehlung für den passenden Klemmhebel.

Form IS: with internal hexagon

Adjustable SM 1720 clamping levers replace the DIN 912 hexagon socket screws for tube clamp connectors.

You will find a recommendation for the right clamping lever for each screw position in the dimension tables for the clamp connectors.

l_1	d_1 Ø	l_2	d_2 Ø	h_1	h_2	kg
45	M6	20	10	9	34	0,040
63	M6	20	10	12	44	0,083
63	M8	25	13	12,5	42	0,092
	M8	30				0,096
	M8	35				0,098
	M8	40				0,102
	M8	50				0,104
78	M8	25	13	15	52	0,148
	M8	30				0,150
	M8	35				0,152
	M8	40				0,154
	M8	50				0,156
78	M10	35	16	16	50	0,166
	M10	50				0,175
	M10	55				0,178
	M10	60				0,181
	M10	65				0,185
92	M10	35	16	16	60	0,220
	M10	50				0,229
	M10	55				0,232
	M10	60				0,235
	M10	65				0,238

+49 40 797002 0 |
scholz-mechanik.de |
service@scholz-mechanik.de

519