







Ausführung für: /
version for:

k = 20
k = 25

k = 14
k = 16

Zylinderschraube
DIN 912 /
socket cap screw



Catalog No.	d ₁	X	d ₂	Colour/Surface
SM 1753-5	08	X	M05	MT



AL: Aluminium
Zylinderschrauben DIN 912:
Edelstahl, nichtrostend 1.4301

AL: Aluminium

Socket cap screws DIN 912:
stainless steel 1.4301



ELSW = schwarz eloxiert
anodized black

MT = matt, gleitgeschliffen /
matte, ground




mm





RoHS
Konform
Compliant



Klemmgewinde d3 /
clamping thread d3




Anbau-Klemmhalter
SM 1753-5 /
Attachment mounting clamp




Klemmhobelset SM 1759-1 /
Clamping kit

Anbau-Klemmhalter
SM 1753-5 /
Attachment mounting clamp



Sensorhalter SM 1756-2 /
retaining plate

Anbau-Klemmhalter
SM 1753-5 /
Attachment mounting clamp



Halteblech SM 1756-1 /
retaining plate

d1 = Bohrung für Wellentoleranz h11 /
bore for shaft tol. h11

d3 = Klemmgewinde / clamping thread
s = Vierkant / square

Zubehör:
empfohlene Klemmhobelsets SM 1759-1 für
Klemmgewinde d3 /
Accessory:
recommended clamping kits SM 1759-1 für
clamping thread d3



Anbau-Klemmhalter SM 1753-5 sind unter anderem zur Montage von Sensorhaltern SM 1756-2 und Halteblechen SM 1756-1 vorgesehen. Sie besitzen ein Zentralgewinde und ab Bohrung d1 = B15 ein zusätzliches Bohrbild 4 x M4.

Die Klemmschraube ist in der Standardausführung eine Zylinderschraube mit Innensechskant DIN 912. Sie kann durch ein Klemmhobelset SM 1759-1 ersetzt werden (Bestellbezeichnung siehe Maßtabelle).

Attachment mounting clamps SM 1753-5 are primarily designed for mounting sensor holders SM 1756-2 and retaining plates SM 1756-1. They are fitted with a central thread and, with d1 = B15 bore and higher, an additional bore template 4 x M4.

In the standard version the clamping screw is a socket cap screw with hexagonal socket DIN 912. It can be replaced by a clamping kit SM 1759-1 (article code see table of dimensions).

d ₁ Ø h11	d ₂ Ø	d ₃ Ø	k	l ₁	l ₂	l ₃	m	s	SM 1759-1 Zubehör /Accessory für d ₃	kg
08	M05	M4	14	25	13,5	7,5	-	-	SM 1759-1M04X14	0,013
10	M05	M5	16	30	17	8,0	-	V08	SM 1759-1M05X16	0,016
10	M06								SM 1759-1M05X16	0,016
10	M08								SM 1759-1M05X16	0,016
12	M05	M5		32	17	9,0	-	V10	SM 1759-1M05X16	0,017
12	M06								SM 1759-1M05X16	0,017
12	M08								SM 1759-1M05X16	0,016
15	M06	M6	20	40	20,5	12,0	14	V12	SM 1759-1M06X20	0,032
15	M08								SM 1759-1M06X20	0,031
16	M06	M6				11,5		-	SM 1759-1M06X20	0,031
16	M08								SM 1759-1M06X20	0,030
20	M08	M6	25	45	21,5	12,0	17,0	V16	SM 1759-1M06X25	0,051
20	M10								SM 1759-1M06X25	0,051