



Catalog No.	d <sub>1</sub>	d <sub>2</sub>	X	l	Material	Colour
SM 1209	70	M10	X 20	NI	RT	

- Griff: Kunststoff Thermoplast (Polyamid PA), glasfaserverstärkt, temperaturbeständig bis 130° C
- Gewindestift: **ST:** Stahl, verzinkt, blau passiviert  
**NI:** Edelstahl rostfrei, 1.4305
- handle: *plastic Technopolymer (Polyamide PA), glass fibre reinforced, temperature resistant up to 130° C*
- threaded bolt: **ST:** steel, zinc plated, blue passivated  
**NI:** stainless steel, 1.4305

- Griffkörper: schwarzgrau, matt, ähnlich RAL 7021  
handle: black-grey, matt similar to
- Farbe Abdeckkappe: colour of the cap:
  - SG** = schwarzgrau / black-grey RAL 7021 ●
  - OR** = orange / orange RAL 2004 ●
  - GR** = grau / grey RAL 7035 ●
  - GB** = gelb / yellow RAL 1021 ●
  - RT** = rot / red RAL 3000 ●
  - BL** = blau / blue RAL 5024 ●

Verhältnismäßig hohe Anzugsmomente, gute Handhabung durch leichte Einbuchtung an den Flügelenden, Gestaltungsmöglichkeiten durch verschiedenfarbige Abdeckkappen.

*A relatively high torque can be achieved. Slight dimple near the wing ends is for good handling.*

mm



d <sub>1</sub> Ø	d <sub>2</sub> Ø	l		d <sub>3</sub> Ø	b	h <sub>1</sub>	h <sub>2</sub>	kg					
		ST	NI										
48	M05	16	-	13,5	7	24	5,5	0,010					
		20	-					0,011					
		M06	16					-	0,012				
			20					20	0,013				
			25					-	0,014				
			30					30	0,015				
	M08	40	-					0,016					
		16	-					0,014					
		20	20					0,016					
		25	-					0,017					
		30	30					0,018					
		40	40					0,019					
55	M08	20	20	16	8	28	6,5	0,023					
		30	30					0,025					
		40	40					0,030					
		M10	20					-	0,032				
			30					-	0,035				
		40	-					0,040					
	63	M08	20					-	19	9	32	7,5	0,031
			30					-					0,033
40			-	0,036									
M10			20	20	0,036								
			30	30	0,042								
40			-	0,048									
70		M08	20	-	20	10	36	8,0					0,035
			30	-									0,037
	40		-	0,040									
	M10		20	20					0,041				
			30	30					0,045				
	40		40	0,049									